

## **viewMT-101** the tough touch screen



10.4"

with a wide viewing angle

## robust

tested for temperature, vibration and ingress protection to withstand the toughest conditions

## variable

adjustable back light and sunlight readable

#### excellent visibility

Improve safety around your vehicle with the display of clear and detailed footage. With **high quality imagery** and a small footprint, the viewMT-101 adds enormous value without impacting cabin real estate.

To ensure consistently good visibility, the LCD touch screen is **sunlight readable** and offers backlight control, removing any night-blindness issues. An internal speaker allows **audio and warning tones** to be easily heard.

The viewMT-101 operates from 9V to 34V DC and has load dump and transient **protected power** input, allowing direct connection to vehicle power.

The screen uses a DEUTSCH MIL Spec connector and industry standard 75mm VESA mounting to maintain the rugged integrity of the product.

The resistive touch screen is extremely **durable** and has a typical operating power of less than 11 watts.

Designed for rugged environments, the viewMT-101 is completely water and dust proof, can handle continuous vibration, and copes with shock and extreme temperature.



# viewMT-101

### technical specifications (extract)

display	<ul> <li>» 10.4"/26.4cm, 4:3 aspect ratio</li> <li>» 1024x768</li> <li>» 1200:1 typical contrast ratio</li> <li>» 24 bit colour depth</li> <li>» 700nits brightness typical</li> <li>» Viewing angle horizontal: 176 deg, Vertical 176deg typical</li> </ul>	sunlight readable touch screen connect up to two displays to the tigerMX-5 vision server
controls	» Backlight brightness » Touch screen, 5-wire resistive touch » Front-mounted panel speaker	
touch screen	<ul> <li>» 2048x2048 touch points</li> <li>» Response time 20ms</li> <li>» &lt;1N with 0.8mm stylus operating force</li> <li>» tested to 10,000,000 touches and 1,000,000 knocks</li> </ul>	
environmental	<ul> <li>» Temp operating: -20C to 65C</li> <li>» Temp storage: -20C to 80C</li> <li>» Humidity: 10% to 90% RH non condensing</li> <li>» IP65</li> <li>» No damage with a 9g steel ball dropped inter the centre of the panel</li> </ul>	
	from a height of 30cm » Static load: 5kg load over a 10 mm area for 10 seconds	
power supply	» 9V to 34VDC (supplied by tigerMX-5)	IP65 rating
size and weight	» Dimensions: 264mm(W)x224mm(H)x42mm(D) » Weight: 1450g	
warranty	» One year	

Specifications subject to change // © Black Moth Vision Systems 2018



#### Vision in Motion

Black Moth's intelligent mobile vision and communication solutions improve worksite safety for heavy machinery. We provide cutting-edge technology and rugged products to support operations in a wide range of transport and heavy industries.

Black Moth Vision Systems Pty Ltd Brisbane Technology Park 42 McKechnie Drive Brisbane 4113, Australia



📞 +61 7 3053 8163 🛛 🗹 hello@blackmoth.com

www.blackmoth.com